



At the Lab. In the Field.
By Your Side.

Krytol Waterstop Grout

Material Safety Data Sheet
May 2008



**CONCRETE
WATERPROOFING**

QUESTIONS: 1-800-267-8280 or www.kryton.com

Section I – Product Identification

Product Code: **K-322**
Product Name: Krytol Waterstop Grout
Intended Use: Concrete Treatment
WHMIS: D2b (materials causing other toxic effects: skin or eye irritant)
TDG: Not regulated

Section II – Hazardous Ingredients

Ingredient:	% by weight	CAS#	Exposure Limits ACGIH TLV - TWA
silica, crystalline, quartz	15-40	14808-60-7	0.05 mg respirable dust/ m ³
portland cement	15-40	65997-15-1	10 mg total dust / m ³

Section III – Physical Data

Colour: Grey
Appearance: Powder
Physical State: Solid
Odour: Odourless
Vapour Density: Not applicable
(compared to air=1)
Soluble in Water: 5-15%
Boiling Point: N/D
Specific Gravity: 1.2
pH: Not available

Section IV – Fire and Explosion Data

Flammable (Y/N): No
Flash Point and Method: Not applicable
Hazardous Combustion Products: None
Firefighting Measures: Use methods for surrounding fire; material will not burn.

MATERIALS SAFETY DATA SHEET

Section V – Reactivity Data

Chemical Stability:	Stable
Reactivity:	Becomes caustic when mixed with water
Incompatibility with other substances:	Mixture with strong acids and bases will cause rapid decomposition which may release CO or CO ₂
Hazardous Decomposition Products:	None

Section VI – Health Hazard Data

Route(s) of exposure:	Eyes, skin, inhalation, ingestion
Exposure Limits:	TWA 10 mg per cubic meter of airborne dust
Acute Exposure Effects:	Contact with eyes will cause severe irritation; wet material may cause irritation of the skin; inhalation of dust may cause respiratory tract irritation.
Chronic Exposure Effects:	Prolonged inhalation of silica dust has been known to result in silicosis. Prolonged or repeated exposure of wet material to the skin may cause chemical burns.
Mutagenicity:	No data
Carcinogenicity:	No data
Irritancy:	Moderate
Sensitization:	N/D

Section VII – Preventative Measures

Protective Clothing to be Worn:	Wear protective goggles, long sleeves and rubber gloves
Respirator:	Dry material may produce airborne dust which may require a dust mask.
Ventilation:	Adequate ventilation must be provided for all enclosed work spaces.
Storage:	Store in the original sealed container.
Spill Procedures:	Replace in the original sealable container
Disposal Procedures:	Dispose of in accordance with local regulations.

Section VIII – First Aid Measures

Skin contact:	Flush with large amounts of clean water, use non-abrasive soap if available. Remove any contaminated clothing. If irritation persists, seek medical attention.
Eye Contact:	Remove any contact lenses. Flush with large amounts of clean water for 15 minutes. If irritation persists, seek medical attention.
Inhalation:	Immediately move victim to fresh air.
Ingestion:	Do not induce vomiting. Guard against aspiration into lungs. Get prompt medical attention. Material is not toxic. If victim is conscious and alert, give two glasses of water.

In case of a dangerous goods emergency, call: (613) 996-6666

Prepared by: Kryton International Inc., May 2008